

Fab 8 ACOUSTICAL FABRIC DUCTING

Fab 8

This non-insulated flexible duct produced using a tough CPE polymeric film core mechanically locked together by a corrosion resistant galvanized steel helix. This acoustically rated, self-extinguishing CPE smooth core duct is a viable solution for most heating, ventilating and air conditioning systems.

Suggested Specification

Flexible duct shall be Fabriflex® Type 8 by Flexmaster. It will be constructed of an acoustically rated CPE polymeric film core mechanically locked to a corrosion resistant external steel helix. Flexible duct connections will be listed in accordance with UL-181 and classified as Class 1 Air Duct.



- Mechanically bonded
- UL listed
- Acoustically rated
- No adhesives
- Core will not aid mold & mildew growth
- Corrosion resistant galvanized steel helix
- Extremely resilient
- Lightweight

Material:	CPE core
Maximum Rated Velocity:	5500 F.P.M
Maximum Positive Pressure:	10" w.g. positive
Maximum Negative Pressure:	5" w.g. negative 1" w.g. for 18" and 20" diameter
Temperature Range:	-20°F to +250°F
Bend Radius:	1 x diameter
Available Sizes:	3" to 20" (Larger sizes on request)
Standard Lengths:	25ft
UL Listing:	UL-181 Class 1 Air Duct

NOTE: This UL Class 1 product has a flame spread rating of not over 25 without evidence of continued progressive combustion and a smoke developed rating of not over 50.

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.