

Fab 5M FLEXIBLE FABRIC DUCTING

Fab 5M

This insulated flexible air duct is a reinforced aluminized trilaminate, mechanically locked together by a corrosive resistant galvanized steel helix. The core is covered with thick fiberglass insulation, and sleeved by a flame retardant, scrim foil mylar sleeve. The reinforced metallized vapour barrier improves puncture resistance and overall duct strength. This ULC-S110 product combined with a reinforced liner and thermal attributes produce a duct assembly ideal for energy efficient HVAC installations.

Suggested Specification

Flexible duct shall be Fabriflex® Type 5M by Flexmaster. It will be constructed of a reinforced aluminized trilaminate which is mechanically bonded to a corrosive resistant outside metal helix. The core will be factory wrapped with thick fiberglass insulation and covered by a flame retardant, scrim foil mylar sleeve. Flexible insulated duct connections will be listed in accordance with ULC-S110 and classified as Class 1.



- Mechanically bonded
- Metallized vapour barrier
- ULC Listed as a Class 1 Air Duct
- Reinforced ducting
- No adhesives
- Core will not aid mold & mildew growth
- Exceptional strength
- Low permeability barrier
- Air tight and leak proof core
- Corrosive resistant helix
- Lightweight
- Thermal reliability
- Insulated

Core Material:	Basic Fab 5
Thermal Resistance:	Available R4.2, R6, R8
Maximum Rated Velocity:	20.3 m/s (4000 fpm)
Maximum Positive Pressure:	1.5 kPa (6 in. WC)
Maximum Negative Pressure:	0.13 kPa (0.5 in. WC)
Temperature Range:	-20°F to +250°F (-29°C to +122°C)
Bend Radius:	1 x diameter
Available Sizes:	3" to 20" (larger sizes on request)
Standard Lengths:	25ft
ULC Listing:	Class 1 Connector

NOTE: This ULC Class 1 product has a flame spread rating of not over 25 without evidence of continued progressive combustion and a smoke developed rating of not over 50.

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.