

#8 Flexmaster PVS Duct Sealer

#8 Flexmaster PVS Duct Sealer

is a tough flexible water based duct sealant. The sealant is for use on flexible air ducts or air connectors and metal duct systems. This product can be used for sealing low, medium and high- pressure heating and air conditioning ductwork. #8 Flexmaster PVS Duct Sealer is suitable for outdoor use. May not be suitable for use with solvent fume exhaust, testing recommended.



Color: White

Appearance: Soft, Creamy white paste

Coverage: Apply at a width of 2-3 inches at a rate of 35 sq. ft. per gallon (0.55 inch wet thickness).

Weight Per Gallon: 11.1 lb.

Average Non-Volatile: 61.5% By Weight

Drying Time: Touch: 30 minutes. Allow at least 72 hours drying time for above applications before pressure testing. Since field temperatures and humidity conditions may vary from controlled lab conditions, longer set times may be required for specific installations.

Safety: Wet: Water based, Non-Flammable

Caution: Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Do not take Internally. In an emergency, call a physician. Keep out of reach of children.

Clean-Up: Wet: Hot soapy water

Service Temperature: -20°F to 180°F

Limitations: Keep from freezing. Apply between 40°F (4°C) and 130°F (54°C)

Application Method: Stiff brush, putty knife, trowel, caulking gun or power extrusion.

Direction For Use: This product is for industrial use only. It should be applied by trained and qualified craftspeople. Be sure all surfaces are clean, dry and oil free. #8 Flexmaster PVS Duct Sealer should be applied at a width of 2-3 inches at a rate of 35 sq.ft. per gallon (0.55 inch wet thickness).

VOC Report: VOC= 0.18lbs/gal.

Or 22.0 Grams/Liter. Meets LEED™ requirements for Credit EQ 4.1

Specification Compliance: NFPA 90A & 90B. UL LISTED 2S04. UL181A-M UL181B-M.

WARRANTY TERMS: The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change without notice. To be sure information is current call Flexmaster Canada Limited.

Terms of Warranty: Warrantor, Flexmaster Canada Limited, warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon test and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE.

Canada

CALGARY, ALBERTA	TORONTO, ONTARIO	DELTA, BRITISH COLUMBIA
Tel 403.277.3115	Tel 416.679.0045	Tel 604.940.6401
Fax 403.276.1309	Fax 416.479.0051	Tel 604.940.6402

MONTREAL, QUEBEC	RICHMOND HILL, ONTARIO	AJAX, ONTARIO
Tel 514.697.3701	Tel 905.731.9411	Tel 905.686.5200
Fax 514.697.3767	Fax 905.731.7086	Fax 905.686.8349