

Flexmaster®

Gear Clamps

Gear Clamp Solution

Offers both maximum strength and anti-shear protection, providing both a practical and cost effective solution.

Ideal for properly securing Triple Lock™ flexible duct connections.

Available in diameters ranging from 2" to 24".

Excellent for mechanical maintenance programs when service is required. The use of gear clamps with Triple Lock™ flex will offer a re-usable solution eliminating the need for replacement flex. When properly used, this fully adjustable clamp will provide constant tension.

Clamps come with a $\frac{5}{16}$ " hex slotted head and $\frac{1}{2}$ " wide stainless steel band.

Specifications

Screw: $\frac{5}{16}$ " hex-head. 410 Stainless steel.

Band: $\frac{1}{2}$ " band width. 210 Stainless steel.

Housing: 20 Stainless steel.

Rated Maximum Torque: 81 in lbs - 6.75 ft lbs - 9.15Nm

Recommended Installation Torque: 45-65 in lbs - 5.1-7.2Nm



Due to continuous improvements, technical data subject to change without notice. All products manufactured by Flexmaster Canada Ltd® are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all products under conditions that duplicate the service conditions prior to installation. Please defer to Flexmaster terms and conditions of sale located at: www.novaflex.com/TermsConditions/

05.2015

IN CANADA

Richmond Hill, Ontario

20 East Pearce Street
Richmond Hill, ON L4B 1B7
tel (905)731-9411
fax (905)905-731-7086



Email: sales@novaflex.com
Website: www.novaflex.com