

# **Novaflex®**

## **Specialty Fume Control**

### Novaflex 1115

A lightweight extremely flexible duct designed specifically to handle today's extremely noxious fumes including fluorine. Ideal for both wet fumes or dry fumes. Good abrasion resistance for exhaust with particulate. Good tear and puncture resistance. Excellent cold temperature resistance. Diesel exhaust extraction where temperature permits. Extreme chemical resistance.

#### Construction

Product code: 3UL1115 Material: 100% PTFE

Construction: Double ply bonded film mechanical lock,

stainless steel helix

Diameters: 4'' to 24'' I.D. larger sizes available Bend radius:  $1.5 \times I.D$ . Weight: 6'' I.D. = .9 lbs/ft

Length: 25 ft. Compression: 4:1

Temperature Range: -5°F (-129°C) to +400°F (204°C).

Continuous +500°F (intermittent)
Colour: Blue, also available in black



## **Specification Chart**

I.D.	4	5	6	8	10	12
Working Pressure/PSI	4	3	2.3	1.4	1	.75
Negative Pressure. H.g.	2.1	1.6	1.2	.6	.4	.3
Weight per Foot	.6	.75	.9	1.2	1.5	1.5

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: <a href="https://www.novaflex.com">www.novaflex.com</a> | <a href="https://www.flex.master.com">www.flex.com</a> | <a href="https://www.flex.master.com">www.flex.com</a> | <a href="https://www.flex.master.com">www.flex.com</a> | <a href="https://www.flex.master.com">www.flex.master.com</a>.

12.2022

#### **IN USA**

#### North Carolina 449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270

#### **New Jersey**

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

#### Indianapolis

7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288

#### IN CANADA

**Ajax, Ontario** 555 Beck Crescent Ajax, ON L1Z 1C9 tel (905)686-5200 fax (905) 686-8349 800-563-3539

#### IN U.K.

#### Bromborough, Wirral

18 Plantation Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk



Email: sales@novaflex.com Website: www.novaflex.com