

# Novaflex®

# Novaflex AP60

## Novaflex AP60 (All Purpose)

An extremely flexible and compressible all around heavy duty duct. With enhanced chemical and temperature resistance of TPR, with an extremely smooth interior for superior flow. A heavy duty external wire encapsulated wear strip protects against abrasion - but will not scuff or mark surfaces.

### Applications

Industrial and residential duct cleaning  
In plant dust control  
Shop vacuum systems  
Chemical fume control

### Product Specifications

Product code: 9NFAP60  
Material: 0.060" extruded thermo plastic rubber  
Diameters: 2" to 12"  
Weight: 1.1 lbs/ft - 6" diam.  
Lengths: 25 ft & 50 ft to 8" diam., 25' - 10" diam. and up  
Compression Ratio: 2:1  
Temperature range: -60°F (-51°C) to +225°F (107°C)  
Colour: Black, with black external wear strip.



## Specification Chart

Size ID (in)	Min in. for 90° Bend	Bend Radius	Friction Loss Straight Run 100' (in Wg)	Friction Loss 90° 100' (in Wg)	Positive W. P. (PSIG)	Neg. W.P. (vacuum rating in Hg)	Wgt (per foot)
2"	8.0"	3.0"	1.68	1.8	8.5	26	0.4
3"	9.0"	3.5"	1.6	1.72	7.5	24	0.57
4"	11.5"	4.5"	1.3	1.43	7.3	20	0.7
5"	13.5"	5.5"	1.23	1.34	7.2	16	0.93
6"	14.5"	6.5"	1.2	1.32	7	12	1.1
8"	19.0"	8.5"	0.7	0.77	6.7	5	1.6
10"	21.0"	10.0"	0.68	0.75	5.5	4.5	2.2
12"	24.5"	11.5"	0.65	0.72	4.7	4	2.73

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: [www.novaflex.com](http://www.novaflex.com) | [www.z-flex.com](http://www.z-flex.com) | [www.flexmaster.com](http://www.flexmaster.com).

04.2021

## IN USA

### North Carolina

449 Trollingwood Road  
Haw River, NC 27258  
tel (336)578-2161  
fax (336)578-5554  
800-334-4270

### New Jersey

1024 Industrial Drive  
West Berlin, NJ 08091  
tel (856)768-2275  
fax (856)768-2385  
800-225-0215

### Indianapolis

7812 Moller Road  
Indianapolis, IND 46268  
tel (317)334-1444  
fax (317)334-1535  
800-526-6288

## IN CANADA

### Ajax, Ontario

555 Beck Crescent  
Ajax, ON L1Z 1C9  
tel (905)686-5200  
fax (905) 686-8349  
800-563-3539

## IN U.K.

### Bromborough, Wirral

18 Plantation Park 2, Power Road  
Bromborough, Wirral UK CH62 3QT  
tel 44(0)151-334-0873  
fax 44(0)151-334-7145  
www.novaflex.co.uk Email: sales@novaflex.co.uk