

Novaflex®

SF LFC - Leaf Collector

SF-TPU .045 thou wall Urethane Leaf Collector Hose

An economical alternative to cumbersome rubber hose. Polyurethane wall for superior abrasion resistance. UV stabilized for outdoor use. Lightweight, good flexibility, smooth interior for optimum flow. Encapsulated wire helix.

Applications:

Leaf collection equipment
Medium duty material handling
Plant debris collection

Construction:

Material: 0.045" translucent blue urethane, encapsulated wire
Diameters: 2" (51mm) to 18"(457.2mm)
Weight: 6" (152mm) = 1.4 lbs/ft (.635k), 8"(203mm) = 1.9 lbs/ft (.86k)
Lengths: Up to 8" (203mm) diameters 25 ft (7.62m) & 50 ft (15.24m) 10" (254mm) diameters and up 25 ft (7.62m)
Compression Ratio: 2:1
Temperature range: -65°F (-54°C) to +200°F (+93°C)
Colour: Blue with blue wear strip.
Also available in black & clear; minimum quantity required.



**Also available in 0.060" gauge clear 8" (203mm) to 14" (356mm) diameter.*

Specification Chart

I.D."	Part No.	Length	Wall	Vacuum
6	9SFTPUW06HW	25', 50'	0.045	23 Hg
8	9SFTPUW08HW	25', 50'	0.045	13 Hg
10	9SFTPUW10HW	25'	0.045	6 Hg
12	9SFTPUW12HW	25'	0.045	5 Hg
14	9SFTPUW14HW	25'	0.045	5 Hg
16	9SFTPUW16HW	10', 12', 25'	0.045	2 Hg
18	9SFTPUW18HW	10', 12', 25'	0.045	1 Hg

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

10.2020

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk