

# Novaflex® Nitrile Food 150 Suction & Discharge

## Novaflex 6300

### Nitrile Food 150 Suction & Discharge Hose

Recommended for the food transfer application that demands both flexibility and ruggedness with a clean white FDA grade tube. Meets FDA, USDA & 3A sanitary standards Authorized #1376. The food grade nitrile tube is odorless and tasteless for those oily transfer applications. Excellent for suction and discharge applications. This ultra smooth microbe resistant tube is built on special stainless steel mandrels for cleanliness.

#### Construction:

Tube: FDA white nitrile

Reinforcement: Multiple plies of polyester tire cord with helix wire

Cover: Grey PVC nitrile. Length: 100ft.

Temperature Range: -40°F (-40°C) to +210°F (+99°C)

(Cleaning In Place to 248°F (+120°C))

Not for continuous steam service.

Meets or exceeds the requirement of the Canadian Food Inspection Agency (File:N267)

Non-stock orders - (other color hose covers red, black, white) are available and require a 400ft minimum order per I.D.



## Specification Chart

Part No.	I.D.	O.D.	Plies	WP psi	MBR	WT LBS/FT
6300WT-00750-00	¾	1.25	2	150	4	0.4
6300WT-01000-00	1	1.50	2	150	5	0.5
6300WT-01500-00	1½	2.00	2	150	6	0.71
6300WT-02000-00	2	2.50	2	150	7	0.95
6300WT-03000-00	3	3.52	2	150	9	1.51
6300WT-04000-00	4	4.52	2	150	12	1.98

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: [www.novaflex.com](http://www.novaflex.com) | [www.z-flex.com](http://www.z-flex.com) | [www.flexmaster.com](http://www.flexmaster.com).

03.2020

## IN USA

### North Carolina

449 Trollingwood Road  
Haw River, NC 27258  
tel (336)578-2161  
fax (336)578-5554  
800-334-4270

### New Jersey

1024 Industrial Drive  
West Berlin, NJ 08091  
tel (856)768-2275  
fax (856)768-2385  
800-225-0215

### Indianapolis

7812 Moller Road  
Indianapolis, IN 46268  
tel (317)334-1444  
fax (317)334-1535  
800-526-6288

## IN CANADA

### Ajax, Ontario

555 Beck Crescent  
Ajax, ON L1Z 1C9  
tel (905)686-5200  
fax (905) 686-8349  
800-563-3539

## IN U.K.

### Bromborough, Wirral

18 Plantation Park 2, Power Road  
Bromborough, Wirral UK CH62 3QT  
tel 44(0)151-334-0873  
fax 44(0)151-334-7145  
[www.novaflex.co.uk](http://www.novaflex.co.uk) Email: [sales@novaflex.co.uk](mailto:sales@novaflex.co.uk)