

# Novaflex®

# **EPDM Food Hose**

## Novaflex 6400

### EPDM Food 150 Suction & Discharge Hose

Recommended for the food transfer application that demands both flexibility and ruggedness with a clean white FDA grade tube. The food grade EPDM tube is odorless and tasteless for non-oily transfer applications. Excellent for suction and discharge applications. This ultra smooth microbe resistant tube is built on special stainless steel mandrels for cleanliness.

## **Specifications**

Tube: FDA white EPDM (non oily applications)

Reinforcement: Multiple plies of polyester tire cord with wire helix

Cover: Gray EPDM. Length: 100ft

Temperature Range: -40°F (-40°C) to +225°F (+107°C)

Not for continuous steam service

Non-stock orders - (other color hose covers white, green, red, yellow, blue, orange black, purple) are available and require a 400ft minimum order per I.D.



Meets or exceeds the requirement of the Canadian Food Inspection Agency (File: N267)

## **Specification Chart**

| Part No.        | I.D. | 0.D. | Plies | WP<br>psi | MBR | WT<br>LBS/FT |
|-----------------|------|------|-------|-----------|-----|--------------|
| 6400WE-00750-00 | 3/4  | 1.29 | 2     | 150       | 4   | 0.4          |
| 6400WE-01000-00 | 1    | 1.54 | 2     | 150       | 5   | 0.5          |
| 6400WE-01500-00 | 1½   | 2.05 | 2     | 150       | 6   | 0.71         |
| 6400WE-02000-00 | 2    | 2.55 | 2     | 150       | 7   | 0.95         |
| 6400WE-03000-00 | 3    | 3.67 | 2     | 150       | 12  | 1.51         |
| 6400WE-04000-00 | 4    | 4.71 | 2     | 150       | 16  | 1.98         |

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete

Terms and Conditions of Sale located on our web sites at: <a href="https://www.novaflex.com">www.novaflex.com</a> | <a href="https://www.flex.master.com">www.flex.master.com</a>.

03.2020

#### **IN USA**

North Carolina 449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270

#### **New Jersey**

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

#### Indianapolis

7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288

#### **IN CANADA**

Ajax, Ontario 555 Beck Crescent Ajax, ON L1Z 1C9 tel (905)686-5200 fax (905) 686-8349 800-563-3539

#### IN U.K.

## Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk

Email: sales@novaflex.com
Website: www.novaflex.com

