

Novaflex

Corrugated Dock Hose

Novaflex 3265 Corrugated Dock Hose

Specially designed for barge unloading where flexibility and ease of handling are required. Special tire cord reinforcement with dual wire helix and corrugated cover enhances the characteristics.

Construction:

Tube: NBR

Reinforcement: Polyester tire cord, dual wire helix.

Cover: Black NBR/PVC corrugated

Ends: Straight.

Length 100 ft (max)

Temperature range: -30°F to +200°F



Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3265-06000-00	6	7.20	4	30	30"	225	7.20
3265-08000-00	8	9.30	6	42	30"	225	10.84
3265-10000-00	10	11.50	6	60	30"	225	13.40
3265-12000-00	12	13.80	8	72	30"	225	17.25

Meets USCG requirements

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

Rev 12.2016

Ajax, ON
Indianapolis, IN
Haw River, NC
Berlin, NJ

Tel 905.686.5200
Tel 317.334.1444
Tel 336.578.2161
Tel 856.768.2275

Fax 905.686.8349
Fax 317.334.1535
Fax 336.578.5554
Fax 856.768.2385

800.526.6288
800.334.4270
800.225.0215

THE
NOVAFLEX
GROUP