

Novaflex

Novalite 3477 Petroleum Transfer Hose

Novaflex 3477 "Novalite"

is recommended for the transfer of petroleum products with an aromatic content of up to 55%. Novalite has a unique design utilizing a flat corrugation design permitting extreme ease when flexing. Novalite is excellent for the transfer of other oily products, such as fats, greases, vegetable oil, hydraulic fluid and a wide range of chemicals.

This hose takes a very little force to flex the hose as compared to other constructions.

Construction:

Reinforcement: Multiple plies of Polyester tire cord with dual helix wire

Cover: Black Oil & Abrasion Resistant Rubber

Length: 100ft (maximum)

Temperature range -40° to +180°F



Product No	ID"	OD"	Plies	WP	MBR	Wt/Ft
3477BT-01000-00	1	1.55"	2	150 psi	2"	.6 lb
3477BT-01250-00	1¼	1.80"	2	150 psi	3"	.7 lb
3477BT-01500-00	1½	2.15"	2	150 psi	3"	5.9 lb
3477BT-02000-00	2	2.68"	2	150 psi	4"	1.2 lb
3477BT-02500-00	2½	3.20"	2	150 psi	5"	1.45 lb
3477BT-03000-00	3	3.73"	2	150 psi	6"	1.9 lb
3477BT-04000-00	4	4.73"	2	150 psi	9"	2.6 lb
3477BT 06000 00	6	6.75"	4	150 psi	20"	5.31 lb

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

12.2017

Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Haw River, NC Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX[®]
GROUP 

Email: sales@novaflex.com
Website: www.novaflex.com