

Novaflex 3550 Petroleum Tank Truck Hose

Novaflex 3550 Heavier Duty Petroleum Discharge Hose

Designed to be flexible with a hose cover that provides extra abrasion resistance to meet the demanding requirements of industry. Handles all grades of petroleum with aromatic contents to 55%.

Construction:

Tube: Black Nitrile

Reinforcement: Multiple plies tire cord with static wire

Cover: Black oil and abrasion resistant rubber

Length: 100 ft.

Temperature Range: -30°F to +180°F



Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3550BT-01000-00	1	1.52	2	n/a	n/a	250	0.57
3550BT-01500-00	1½	2.14	2	n/a	n/a	250	0.96
3550BT-02000-00	2	2.64	2	n/a	n/a	250	1.23
3550BT-02500-00	2½	3.14	2	n/a	n/a	250	1.49
3550BT-03000-00	3	3.54	2	n/a	n/a	250	2.10
3550BT-04000-00	4	4.65	4	n/a	n/a	250	2.42
3550BT-06000-00	6	6.70	4	n/a	n/a	250	4.90

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

rev.01.2018

Indianapolis, IN
Haw River, NC
Berlin, NJ
Ajax, ON

Tel 317.334.1444 Fax 317.334.1535
Tel 336.578.2161 Fax 336.578.5554
Tel 856.768.2275 Fax 856.768.2385
Tel 905.686.5200 Fax 905.686.8349

800.526.6288
800.334.4270
800.225.0215

NOVAFLEX[®]
PROVIDING HOSE & DUCT SOLUTIONS

Email: sales@novaflex.com
Website: www.novaflex.com