

Material Handling Hose

Novaflex 5016 (Vacuum Only)

Material Handling Hose 1/4" Gum Tube

Heavy duty material handling hose designed for portable and central industrial vacuum equipment as well as truck mount applications. The 1/4" abrasion resistant tube is designed to resist cutting, tearing and wear from abrasive media. The heavy helix wire is designed to resist kinking and crushing as well as handle full vacuum. (Ground using helix wire to make static conductive.)

Construction:

Tube: 1/4" tan gum

Reinforcement: Plies of fabric with helix wire.

Cover: SBR Black Corrugated

Length: 50 ft. Ends: Plain or soft cuffs.

Temperature Range: -40°F to +140°F

Novaflex 5016YG = Yellow Novaware tube
superior abrasion resistance



Part No.	I.D.	O.D.	MBR (in)	VAC (Hg)	WT LBS/FT
5016BG-02500-00	2½	3.38	9	29"	2.0
5016BG-03000-00	3	3.88	12	29"	2.2
5016BG-04000-00	4	4.88	24	29"	3.0
5016BG-06000-00	6	6.88	36	29"	4.1
5016BG-08000-00	8	8.88	48	17"	7.2
5016BG-10000-00	10	10.88	60	9"	9.0
5016BG-12000-00	12	12.88	72	9"	11.4

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

ver 01.2018

Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Haw River, NC Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX[®]
 GROUP

Email: sales@novaflex.com
 Website: www.novaflex.com