

Novaflex®

Roof Drain Hose

Roof Drain Hose

Manufactured for use in tanks with floating roof drain systems. Roof Drain Hose works well as a flexible elbow as it easily bends 90°. Also suitable for oil skimmers, suction lines and water separators. Compatible both inside and out for a wide range of PH solutions and chemicals.

Available in 1" to 4" diameters

Operating Temperature: -40°F to +212°F / -40°C to 100°C

Inner Wire: High Tensile Galvanized Wire

Outer Wire: 316 Stainless Steel Wire

Outer Cover: UHMW Cover



Specification Chart

ID(Inches)	Max WP(Bar)	Bend Radius (mm)	Weight Kg/M	Max length (M)
3	14	208	2.89	40
4	14	302	3.99	40
6	14	560	10.73	35

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation. For complete guide to proper care, use and maintenance see Care & Maintenance Guide @2003-1 at www.novaflex.com. Please defer to Novaflex terms and conditions of sale located at: www.novaflex.com/TermsConditions/

08.2016

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk