

Uni-Chem™ Bottom Loading Service



Uni-OIL™ is ideal for transferring petroleum and 100% aromatic products in production, refinery and distribution facilities. Suitable for all hose loading arms in bottom loading operations. Constructed with multiple plies of aromatic resistant films and fabrics.

Uni-BL™ Hoses can be custom designed for special chemical applications.

All hoses can be color coded to API color codes

Uni-BL™ GG

G-High Tensile Galvanized Carbon Steel Inner Helix

G-High Tensile Galvanized Carbon Steel Outer Helix

Maximum Length: 100 feet

Operating Temperature:

-40°F to +212°F / -40°C to +100°C

Brown Cover

| INS ID | OUT ID | MAX WP PSI | BURST PRES PSI | BEND RAD. INCHES | WEIGHT LB/FT | MAX LENGTH |
|--------|--------|---------------|-------------------|------------------------|-----------------|---------------|
| 1 | 1.5 | 250 | 1000 | 4.0 | 0.58 | 100 |
| 1.5 | 1.9 | 250 | 1000 | 5.0 | 0.79 | 100 |
| 2 | 2.4 | 250 | 1000 | 6.0 | 1.18 | 100 |
| 3 | 3.4 | 250 | 1000 | 7.9 | 1.88 | 100 |
| 4 | 4.4 | 250 | 1000 | 11.9 | 2.68 | 100 |
| 6 | 7.0 | 250 | 1000 | 22.0 | 7.20 | 100 |
| 8 | 9.4 | 250 | 1000 | 30.0 | 11.00 | 100 |

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation. For complete guide to proper care, use and maintenance see Care & Maintenance Guide @2003-1 at www.novaflex.com. Please defer to Novaflex terms and conditions of sale located at: www.novaflex.com/TermsConditions/

01.2012

Indianapolis, IN
Haw River, NC
Berlin, NJ
Ajax, ON

Tel 317.334.1444
Tel 336.578.2161
Tel 856.768.2275
Tel 905.686.5200

Fax 317.334.1535
Fax 336.578.5554
Fax 856.768.2385
Fax 905.686.8349

800.526.6288
800.334.4270
800.225.0215

NOVAFLEX®
PROVIDING HOSE & DUCT SOLUTIONS
Email: sales@novaflex.com
Website: www.novaflex.com