

Uni-Chem™ Bottom Loading Hose



Uni-VR™ Hose is ideal for use in petroleum and petrochemical vapor recovery systems in ship to shore, bottom loading and tank truck applications. This hose is lightweight and flexible. Manufactured to meet specification CFR33-154. Available with a yellow or orange cover.

Operating Temperature: -40°F to +140°F

Uni-VR™*

G-High Tensile Galvanized Carbon Steel Inner Helix
G-High Tensile Galvanized Carbon Steel Outer Helix
Yellow Cover

*Available with a polypropylene coated and stainless steel inner helix.

INS ID	OUT ID	MAX WP PSI	BURST PRES PSI	BEND RAD. INCHES	WEIGHT LB/FT	MAX LENGTH
1	1.5	250	800	4.0	0.58	100
1.5	1.9	250	800	5.0	0.79	100
2	2.4	250	800	6.0	1.18	100
3	3.4	250	800	7.9	1.88	100
4	4.4	250	800	11.8	2.68	100
6	7.0	250	800	22.0	7.20	100
8	9.4	250	800	30.0	11.00	100

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation. For complete guide to proper care, use and maintenance see Care & Maintenance Guide @2003-1 at www.novaflex.com. Please defer to Novaflex terms and conditions of sale located at: www.novaflex.com/TermsConditions/

01.2012

Indianapolis, IN
Haw River, NC
Berlin, NJ
Ajax, ON

Tel 317.334.1444
Tel 336.578.2161
Tel 856.768.2275
Tel 905.686.5200

Fax 317.334.1535
Fax 336.578.5554
Fax 856.768.2385
Fax 905.686.8349

800.526.6288
800.334.4270
800.225.0215

NOVAFLEX®
PROVIDING HOSE & DUCT SOLUTIONS
Email: sales@novaflex.com
Website: www.novaflex.com