

Uni-OIL 300HT High Temperature Composite Hose



Novaflex Uni-OIL 300HT is a high temperature version of the standard Uni-oil petroleum.

This hose can handle maximum operating temperatures of 300°F. The hose design uses a composite of temperature resistant materials and is rated for use with a wide range of petroleum products.

Specifications

Temperature: up to -40°F (-40°C) to 300°F (149°C)

Working Pressure: 250psi

Reinforcement: Galvanized carbon steel

Standard length: 100 ft

Branding: Black/Red letters

Bend radius: 3" I.D. =8.2"

Weight per/ft: 3" I.D. =2.6lb

Standard color: Red

Hose ID"	Hose OD"	Max WP psi	Burst Pressure	Wt/ft.Lb	Max Length
1	1.5	250	1000	.065	100
3	2.0	250	1000	.85	100
2	2.5	250	1000	1.7	100
3	3.5	250	1000	2.6	100
4	4.5	250	1000	3.4	100
6	7.0	250	1000	7.20	100
8	9.4	250	1000	11.00	80
10	10.5	150	600	14.50	50

Always check Novaflex's *chemical resistance chart* before use. Temperature and or concentration may effect service life. If unsure about the operating conditions please contact Novaflex.

All hose and duct manufactured by Novaflex are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation. Due to continuous improvements, technical data subject to change without notice.

Rev 11.14

Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Haw River, NC Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX[®]
 GROUP
 

Email: sales@novaflex.com
 Website: www.novaflex.com