

## Novaflex 5510 Black Low Pressure Conductive Steam Hose 100psi

This textile reinforced steam hose is an excellent flexible light weight hose for transferring steam in medium temperature applications.

**Construction:**

Tube: Black EPDM

Reinforcement: Plies of fiberglass tire cord

Cover: Smooth black weather and abrasion resistant EPDM

Length: 100 ft.

Temperature Range: Up to +338°F (+170°C)



Part No.	I.D.	O.D.	Plies Fiberglass	WP psi	WT LBS/ FT
5510BE-00500-00	½	1.02	4	100	0.34
5510BE-00750-00	¾	1.27	4	100	0.45
5510BE-01000-00	1	1.52	4	100	0.56
5510BE-01250-00	1¼	1.82	4	100	0.75
5510BE-01500-00	1½	2.07	4	100	0.87
5510BE-02000-00	2	2.57	4	100	1.11

## Novaflex 5520 Red Low Pressure Non-Conductive Steam Hose 100psi

This textile reinforced steam hose is an excellent flexible light weight hose for transferring steam in medium temperature applications that require an electrically non-conductive hose.

**Construction:**

Tube: Red EPDM rubber

Reinforcement: Plies of fiberglass tire cord

Cover: Smooth Red weather and abrasion resistant EPDM rubber

Length: 100 ft.

Temperature Range: Up to +338°F (+170°C)

Non-conductive



Part No.	I.D.	O.D.	Plies Fiberglass	WP psi	WT LBS/FT
5520RE-00500-00	½	1.02	4	100	0.34
5520RE-00750-00	¾	1.27	4	100	0.45
5520RE-01000-00	1	1.52	4	100	0.56
5520RE-01250-00	1¼	1.82	4	100	0.75
5520RE-01500-00	1½	2.07	4	100	0.87
5520RE-02000-00	2	2.57	4	100	1.11
5520RE-03000-00	3	3.76	6	100	2.19