

Water Hose - Fire Engine Suction

Novaflex 2250

High Pressure Water Jetting Hose

Designed for heavy duty, high pressure water jetting. Premium quality compounds provide excellent resistance to the common abuses associated with water jetting in the marine and construction industry.

Construction:

Tube: Black EPDM
 Reinforcement: Polyester tire cord
 Cover: Smooth black EPDM cover Length: 100ft
 Temperature Range: -30° (-35°C) to +180°F (+82°C)



Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2250BE-02000-00	2	2.80	6	800	1.30
2250BE-02500-00	2½	3.30	6	800	1.59
2250BE-03000-00	3	3.80	6	800	1.87
2250BE-04000-00	4	4.84	6	800	2.42
2250BE-05000-00	5	5.92	6	500	2.68
2250BE-06000-00	6	6.92	6	500	3.20

Novaflex 2160

Water Removal and Hydrant Services

Premium quality heavy duty hose designed for suction and discharge applications commonly found in water removal and hydrant service on fire trucks

Construction:

Tube: SBR
 Reinforcement: Multiple plies of polyester tire cord with helix
 Cover: Smooth SBR
 Length: Available in specific lengths with cuff ends - price on application
 Temperature Range: -40° (-40°C) to +180°F (+82°C)
 Meets or exceeds NFPA #189 & 1901 requirements



Part No.	I.D.	O.D.	Plies	WP psi	Min Order Lgth	WT LBS/FT
2160BS-02000-00	2	3.25	2	150	100'	2.46
2160BS-02500-00	2½	3.687	2	150	100'	2.88
2160BS-03000-00	3	4.25	2	150	50'	3.77
2160BS-04000-00	4	4.687	4	150	50'	5.16
2160BS-05000-00	5	5.75	4	150	50'	5.77
2160BS-06000-00	6	6.75	4	150	50'	7.03

Novaflex 2161

Water Removal and Hydrant Services

Premium quality heavy duty hose designed for suction and discharge applications commonly found in water removal and hydrant service on fire trucks.

Construction:

Tube: SBR
 Reinforcement: Multiple plies of polyester tire cord with helix
 Cover: Corrugated black EPDM cover
 Length: up to 100 ft
 Temperature Range: -40° (-40°C) to +180°F (+82°C)
 Hose comes with 6" cuffed ends. Meets or exceeds NFPA #189 & 1901 requirements.



Part No.	I.D.	O.D.	Plies	WP psi	Min Qty	WT LBS/FT
2161BS-02500-00	2	3.04	2	150	4	2.42
2161BS-02500-00	2½	3.54	2	150	4	2.90
2161BS-03000-00	3	4.54	2	150	2	3.47
2161BS-04000-00	4	4.687	4	159	2	5.2
2161BS-05000-00	5	5.54	4	150	2	5.88
2161BS-06000-00	6	6.58	4	150	2	7.36