

Novaflex®

Medium Service Duct

U-Lok 200

Medium weight flexible ducting products with heavier gauge fabric and coating provide additional service life. Neoprene coating provides good cold temperature resistance compared with PVC. Manufactured with UL94V-0 approved materials.

Applications

Heavy-duty dust control
Outdoor plant clean-up
Sawdust, hot air blower

Specifications

Product code: 3UL200X
Material: polyester/neoprene
Construction: Mechanical bond, corrosion resistant
Diameters: 3" to 24" I.D. Larger sizes available
Bend radius: = 1.5 x I.D.
Weight: 6" I.D. - 1.1 lbs/ft
Length: 25ft
Compression Ratio: 6:1
Temperature Range: -65°F (-54°C) to +250°F (+121°C)
Colour: Black



Specification Chart

I.D.	3	4	5	6	8	10	12
Working Pressure/PSI	4.3	4	3.6	3.5	3	2.15	1.8
Negative Pressure. H.g.	3.2	2.7	2.4	2.2	1.8	1.6	1.25
Weight per Foot	.6	.7	.9	1.1	1.5	1.8	2.2

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

11.2019

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk