

Novaflex®

High Temperature Duct

U-Lok 401

The combination of external helix as a scuff guard and a non-glue construction results in the industry standard high-temperature duct.

Applications

Gas exhaust control

Hot fume control

Hot air supply and removal

**A negative pressure fan system with ambient air inlet is recommended to maximize effectiveness and life of duct. It is important to size the duct diameter according to the exhaust output.*

**Not recommended for diesel fume applications.*

Construction

Product code: 3UL401X

Material: Fiberglass/Silicone

Construction: Mechanical bond, corrosion resistant helix

Diameters: 2" to 24" I.D.

Bend radius: = 1.5" x I.D.

Weight: 6" I.D. = 1.1 lbs/ft. Length: 25 ft.

Compression ratio: 5:1.

Temperature range: -65°F (-54°C) to +500°F (260°C) intermittent.

Colour: Metallic Grey

**Also available with stainless steel helix*

**Also available: U-Lok 420, constructed with heavier weight fiberglass and a heavier gauge helix (not shown).*



Specification Chart

I.D.	2	3	4	5	6	8	10	12
Working Pressure/PSI	8	6.8	3.7	3	2.3	1.4	1	.75
Negative Pressure Inch. H.g	7	4.5	2.1	1.6	1.2	.7	.45	.3
Weight per Foot	.24	.34	.4	.5	.68	.98	1.02	1.26

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

11.2019

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk