

Novaflex®

Connoisseurs Food & Beverage Hose

Novaflex 6506

Connoisseurs Food & Beverage Hose

Special kink and crush resistant suction & discharge hose, designed for those more demanding applications requiring a product that meets 3-A (cert# 1803), FDA & USDA standards. FDA (21.177.2600). ADI Free. REACH Compliant. Designed to meet the temperatures and chemical resistance associated with "cleaning in place" systems. This ultra smooth microbe resistant tube is built for non-oily applications, on special stainless steel mandrels for cleanliness.

Specifications

Tube: White Chlorobutyl (non oily applications)
 Reinforcement: Multiple plies of polyester tire cord & dual monofilament helix
 Cover: Gray EPDM abrasion resistant. Length: 100 ft
 Temperature Range: -40°F (-40°C) to +240°F (+116°C)
 (Cleaning In Place to 248°F [+120°C])
 Not for continuous steam service



Meets or exceeds the requirement of the Canadian Food Inspection Agency (File:N267)

Specification Chart

Part No.	I.D.	O.D.	MBR (in)	VAC (Hg)	Plies	WP psi	WT LBS/FT
6506WB-00750-00	¾	1.41	3.0	Full	2	250	0.33
6506WB-01000-00	1	1.64	3.5	Full	2	250	0.44
6506WB-01500-00	1½	2.14	4.5	Full	2	250	0.63
6506WB-02000-00	2	2.77	7.0	Full	4	250	1.21
6506WB-02500-00	2½	3.29	13.0	Full	4	250	1.52
6506WB-03000-00	3	3.79	16.0	Full	4	250	1.84
6506WB-04000-00	4	4.97	24.0	Full	4	250	4.16

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

03.2020

IN USA

North Carolina

449 Trollingwood Road
 Haw River, NC 27258
 tel (336)578-2161
 fax (336)578-5554
 800-334-4270

New Jersey

1024 Industrial Drive
 West Berlin, NJ 08091
 tel (856)768-2275
 fax (856)768-2385
 800-225-0215

Indianapolis

7812 Moller Road
 Indianapolis, IN 46268
 tel (317)334-1444
 fax (317)334-1535
 800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
 Ajax, ON L1Z 1C9
 tel (905)686-5200
 fax (905) 686-8349
 800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
 Bromborough, Wirral UK CH62 3QT
 tel 44(0)151-334-0873
 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk