



Lawrence Marine, part of *The NovaFlex Group* is a North American hose manufacturer, that specializes in marine products. Our 50 plus years of marine experience provide the boat owner with simply the best products to meet the demanding requirements of the boating industry.

Lawrence Marine uses state of the art manufacturing processes to provide the boat owner with a choice of hoses to protect against the release of odors! Most hose will permeate over time! Choose the best hose for your needs based on your required level of odor protection, flexibility and cost.

Sanitation Hose

Good Better **Best**

New

Odor Block
Odor Protector
Heavy Duty PVC

LAWRENCE MARINE
THE NOVAFLEX GROUP 

Odor Block Sanitation Series 104OB

The best rubber sanitation hose available to prevent odor permeation in marine waste systems. New copolymer tube designed to exceed industry requirements and be highly flexible and easy to connect. Suction (full vacuum) and discharge applications.

Operating temperature: -40° to 200°F (-40° to 93°C)

Max Working Pressure: 75psi with worm gear clamps

150 psi with industrial couplings & clamps

150 psi with industrial couplings and bands



Best

Part No.	ID	MM	OD	MM	Min. Bend Radius	Burst psi 70°F (21.1°C)
104CU-01000-OB-600F	1"	25.4	1.47"	37.34	3"	600
104CU-01500-OB-600F	1.5"	38.1	2.08"	52.84	4"	600

Odor Protector Sanitation Series 144

A newly formulated premium PVC resin specifically developed to prevent odor permeation commonly found in marine waste systems. This newly designed resin protects against odor permeation. Highly flexible and compatible with all sanitation systems. Suction and vacuum applications.

Operating temperature: 5° to 158°F (-12° to 70°C)

Max Working Pressure: 50psi with worm gear clamps



Better

Part No	ID	MM	OD	MM	Min. Bend Radius	Max. WP 70°F (21.1°C)
144WL-00750-00-1200	.75"	19.05	.95"	24.13	2"	50 psi
144WL-01000-00-1200	1"	25.4	1.24"	31.5	2"	50 psi
144WL-01500-00-1200	1.5"	38.1	1.80"	45.72	3.5"	38 psi

HD Smooth PVC Sanitation Series 148

A proven hose made from approved resins. This hose has been used for years and is an excellent sanitation hose. Heavy duty thick PVC construction, suction and vacuum applications.

Operating temperature: 0° to 120°F (-12° to 70°C)

Max Working Pressure: 50psi with worm gear clamps



Good

Part No.	ID	MM	OD	MM	Min. Bend Radius	Max WP 70°F (21.1°C)
148WL-00750-00-1200	.75"	19.05	.95"	24.13	2"	50 psi
148WL-01000-00-1200	1"	25.4	1.24"	31.5	2"	50 psi
148WL-01125-00-1200	1.125"	28.58	1.38"	35.05	2.3"	40 psi
148WL-01250-00-1200	1.25"	31.75	1.51"	38.35	2.5"	40 psi
148WL-01500-00-1200	1.5"	38.1	1.80"	45.72	3.5"	38 psi



Lawrence Marine • Novaflex Hose Inc
 Tel: 336-578-2161 Fax: 336-578-5554
 Toll Free: 800-334-4270
www.novaflex.com • email: sales@novaflex.com